

PRODUCT TYPE		GPON ONT	MODEL: TT-G110R
HARDWARE	CPU	CPU Feature	Single core,MIPS interAptiv™1GHz
	Interfaces	LAN port	1* GE port
		PON port	1
		DC port	1
		Reset	1
	Wi-Fi	Standard	IEEE 802.11 b/g/n
		Speed	300Mbps @ 2.4GHz 2T2R
		Antenna	2* External
		Gain	5dBi
	GPON	Standard	ITU-T G.984/G.988
		Wavelength	1310nm/1490nm
		Speed	Upstream rate up to 1.244 Gbit/s, downstream rate up to 2.488 Gbit/s
		Sensitivity	≤-28dBm
		Emission Power	1dBm<P<4dBm
		Distance	20 km
		Connector	SC/UPC or SC/APC
SOFTWARE	Support	Protocols	ITU-T G.984/G.988 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IEEE 802.1w, RSTP IGMP v1/v2/v3 ITU-T Y.1291
		Access Mode	Optional: PPPoE, Bridge, IPoE
		Management	OMCI, TR-069(FreeAcs、GenieAcs)
		Algorithm	SP/WRR/SP+WRR
	Security	Encryption	AES128
		Authentication	CHAP, EAP
		Others	Loopback
OTHERS	Accessories	1 * Power Adaptor	
		1 * Manual	
	Device Parameter	Power Supply	Input 110-240VAC; Output 12VDC/1A
		Power Consumption	<12W
		Net Weight	115g
Size	147mm(L)*92mm(W)*24.5mm(H)		
IMAGE			