

PRODUCT TYPE		XPON ONT	MODEL: TT-X100R1	
HARDWARE	CPU	CPU Feature	Realtek 300MHz	
	Interfaces	LAN port	1 * GE port	
		PON port	1	
		DC port	1	
	XPON	Standard	GPON: ITU-T G.984/G.988 EPON: IEEE 802.3ah, YD/T 1475-2006	
		Wavelength	1310nm/1490nm	
		Speed	GPON: Upstream rate up to 1.244 Gbit/s, downstream rate up to 2.488 Gbit/s	
			EPON: Upstream rate up to 1.244 Gbit/s, downstream rate up to 1.244 Gbit/s	
		Sensitivity	≤-28dBm	
		Emission Power	1dBm ≤ P ≤ 4dBm	
Distance		20 km		
Connector	SC/UPC or SC/APC			
SOFTWARE	Support	Protocols	ITU-T G.984/G.988 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IGMP v1/v2/v3 IEEE 802.1w, RSTP ITU-T Y.1291	
		Access Mode	Optional : PPPoE, Bridge, IPOE	
		Management	OMCI, TR-069(FreeAcs、GenieAcs)	
	Security	Algorithm	SP/WRR/SP+WRR	
		Encryption	AES128	
		Authentication	CHAP, PAP	
	OTHERS	Accessories	Others	Loopback
1 * Power Adaptor				
Device Parameter		1 * Manual		
		Power Supply	Input 110~240VAC; Output 12V DC/1A	
		Power Consumption	<12W	
	Net Weight	52g		
Size	74mm(L) × 74mm(W) × 20mm(H)			
IMAGE				